



338 REMINGTON ROAD  
 CUYAHOGA FALLS, OH 44224  
 Phone: 330.920.3125 Fax: 330.920.3126

# SS-1000

## Product Description

SS-1000 is a fast curing rubber coating developed for shock dampening and vibration isolation applications. SS-1000 is a 2-part silicone that when cured, allows handling of the parts within minutes. SS-1000 works well in manual and automatic dispensing equipment

## Product Features

- Room temperature cure or fast heat cure silicone rubber
- Convenient 1:1 mix ratio
- Pourable and self-leveling
- Platinum addition cure

## Typical Applications

- Vibration isolation
- Severe impact cushioning
- Dampening of severe shock

## Chemical Cure System

Platinum catalyzed, addition cure



# Vibration and Shock Dampening Rubber Coating

## Typical Properties

Color	Translucent
Viscosity, cps	10,000
Specific Gravity	1.05
Consistency	Thick liquid
Work Time @ RT	15 Minutes
Cured @ RT	60-120 Minutes
Cured @ 150°C	5 Minutes
Durometer	<5 Shore A
Tensile Strength	289 PSI

## Handling Precautions

This is a platinum cure system product. The catalyst can be deactivated by exposure to sulfur containing compounds like thiols, sulfides, sulfates, organic rubber containing sulfur, nitrogen containing compounds like amines, amides, imides, azides, tin metals or compounds, or tin cured RTV's.

## **Solids**

**99% solids**

## **Limitations**

**Allow to fully cure before putting assembly into service. Ensure enough product remains between flanges to be effective in an assembly.**

## **Packaging**

**SS-1000 is available in dual syringes, 40 lb pail kits and 400 lb drum kits. This product is also available in customer defined packaging sizes, upon request.**

## **Handling and Safety**

**For maximum shelf life, keep containers sealed when not in use. Keep out of the reach of children. Uncured sealant irritates eyes and skin. Refer to the SDS.**

## **Shelf Life**

**Sealed containers are guaranteed for 12 months from the ship date when stored in a cool dry area below 70°F.**

## **Limited Warranty**

**All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as warranty, either expressed or applied. User shall rely on his/her own information and tests to determine suitability of the product for the intended use, and the user assumes all risk and liability resulting from the use of this product.**

**Manufacturer's sole responsibility shall be to replace that portion of product that the manufacturer proves to be defective.**

**Manufacturer shall not be liable to the buyer or any third party for injury, loss or damage directly or indirectly resulting from the use of, or inability to use, the product. Recommendations or statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding by the manufacturer.**

**This product has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses which implantation within the human body is intended.**

**\*\*\*\*\*Customized versions available upon request\*\*\*\*\***