



338 REMINGTON ROAD
 CUYAHOGA FALLS, OH 44224
 Phone: 330.920.3125 Fax: 330.920.3126

SS-261

Product Description

SS-261 is an electrically conductive, heat curing silicone. SS-261 is a 1-part silicone that when applied to the substrate allows handling of the assembly within an hour. SS-261 works well in manual and automatic dispensing equipment.

Product Features

- Very high electrical conductivity
- Fast heat cure
- Non-Corrosive


Typical Applications

- Form in place gaskets
- Electrically conductive sealant
- EMI/RFI silicone shielding

Chemical Cure System

Platinum catalyzed, addition cure

*****Product must be kept frozen*****



Heat Cure Electrically Conductive Silicone

Typical Properties

Color	Silver-Tan
Viscosity, cps	400,000
Specific Gravity	3.06
Consistency	Heavy Paste
Working Time @ RT	24 Hours
Cure Time @ 115°C	45 Minutes
Durometer	70 Shore A
Volume Resistivity	0.005 Ohms-cm
Thermal Conductivity	>2.5 W/m-K
Conductive Filler	Silver

Curing

Cure speed can be accelerated with heat to very rapid cure times.

Handling Precautions

This is a platinum cure system product. The catalyst can be deactivated by exposure to sulfur containing compounds like thiols, sulfides, sulfates, organic rubber containing sulfur, nitrogen containing compounds like amines, amides, imides, azides, tin metals or compounds, or tin cured RTV's.

Solids

100% solids, contains no solvents

Adhesion

Primerless adhesion to most metals and typical substrates

Limitations

Do not use product in solvent or fuel immersion applications. Allow to fully cure before putting assembly into service. Ensure enough product remains between flanges to be effective in an assembly.

Handling and Safety

For maximum shelf life, keep containers sealed when not in use. Keep out of the reach of children. Uncured sealant irritates eyes and skin. Refer to the SDS.

Shelf Life

Sealed containers are guaranteed for 6 months from the ship date when stored in a freezer.

Limited Warranty

All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as warranty, either expressed or applied. User shall rely on his/her own information and tests to determine suitability of the product for the intended use, and the user assumes all risk and liability resulting from the use of this product. Manufacturer's sole responsibility shall be to replace that portion of product that the manufacturer proves to be defective. Manufacturer shall not be liable to the buyer or any third party for injury, loss or damage directly or indirectly resulting from the use of, or inability to use, the product. Recommendations or statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding by the manufacturer.

This product has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses which implantation within the human body is intended.

*******Customized versions available upon request*******