

# Safety Data Sheet (SDS) Industrial Use Only

# 1. Product and Company Identification

#### **Product:**

Product Name: SS-3001 Silicone Coating RTV Intended Use: Sealant

### Manufacturer/Supplier:

Silicone Solutions 338 Remington Road Cuyahoga Falls, OH **Preparer:** Casey Linx **Chemical Family:** Silicone Rubber **Emergency Telephone Number:** 330-920-3125

# 2. Hazards Identification

### **Classification of the substance or mixture:**

Not classified

### **GHS label Elements:**

**Signal word:** No signal word **Hazard statements:** No known significant effects or critical hazards

#### **Precautionary Statements:**

General: Not applicable Prevention: Not applicable Response: Not applicable Storage: Not applicable Disposal: Not applicable

### **Other Hazard Information:**

• This product can generate formaldehyde upon exposure above 300 degrees centigrade in atmospheres that contains oxygen. Formaldehyde is a skin, eye, and throat irritant.

# 3. Composition/Information on Ingredients

### **Chemical Characterization:**

Formula: Mixture

### Composition and Information on Ingredients: Non-hazardous components of the mixture unless otherwise specified.

Component	CAS #	Approximate % Weight
Vinyl Oximino Silane	2224-33-1	1-5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

# 4. First Aid Measures

#### **General Information:**

Ingestion: If swallowed, do not induce vomiting unless directed to do so by medical personnel. Get medical aid.Skin: Wash with soap and water.Inhalation: If breathing is difficult, remove to fresh air and get medical aid.In case of eye contact: Flush with water for fifteen minutes and get medical attention.

Note to Physician: Treat symptomatically.

## 5. Firefighting Measures

#### **Flammability Properties:**

**Flash Point:** 56°C or 132.8°F **Ignition Temperature:** 752°F **Flammable Limits in Air-Upper % :** NA **Flammability Limits in Air-Lower % :** NA **Sensitivity to Mechanical Impact:** No **Sensitivity to Static Discharge:** Yes

Extinguishing Media: All standard firefighting material.

### Special Firefighting Procedures: None known.

## 6. Accidental Release Measures

Action to be taken if material is released or spilled: Scrape up and place in an inert material for disposal. See Section 8 for protective equipment upon exposure and Section 7 for information on safe handling.

## 7. Handling and Storage

**Precautions to be taken during handling and storage:** Cure only where appropriate ventilation systems exist, as seen in *Section 8*.

# 8. Exposure Controls/Personal Protection

### **Control Parameters:**

Components with limit values that require monitoring at the workplace:

Component	CAS #	ACGIH TWA	TLV STEL	OSHA TWA	PEL STEL
Vinyl Oximino Silane	2224-33-1	NE	NE	NE	NE

**Note:** Oximino Silanes form Methyl Ethyl Ketoxime upon contact with atmospheric moisture. Provide adequate ventilation to control exposures within the following exposure guidelines: *Vendor Guide TWA: 3 ppm, Vendor Guide STEL: 10 ppm, AIHA WEEL TWA: 10 ppm* 

#### **Exposure Controls and Protection:**

**Engineering Controls:** Facilities utilizing this material should be equipped with an eyewash facility and a safety shower. Adequate general or local explosion-proof ventilation is required.

Respiratory Protection: Respiratory protection unless local exhaust ventilation is provided.

Protective Gloves: Cloth gloves.

**Eye and Face Protection:** Safety glasses.

Other Protective Equipment: Wear appropriate clothing to prevent skin exposure.

Ventilation: Cure in well-ventilated areas.

# 9. Physical and Chemical Properties

#### Information on basic physical and chemical properties:

**Boiling Point:** 176°C Vapor Pressure: NA Vapor Density: 10.23 Freezing Point: 17.5°C Melting Point: NA Physical State: Liquid. Odor: Mild. % Volatile by Volume: 50 **Evaporation Rate: NA** Specific Gravity: 1.12 **Density (kg/m<sup>3</sup>):** 1200 Acid/Alkalinity: Neutral. pH: NA **VOC:** < 3 Solubility in Water: Insoluble. Solubility in Organic Solvents: Partially soluble in toluene.

## **10. Stability and Reactivity**

#### **Chemical Stability:**

Stability: Unstable if heated.

#### **Reactivity:**

Hazardous Polymerization: Will not occur.
Hazardous Thermal Decomposition/Combustion Products:
Carbon Dioxide

- Carbon Monoxide
- Silicon Dioxide
- Sincon Dioxide
   Formaldehyde
- Formaldehyde

Conditions to Avoid: None known.

# **11. Toxicological Information**

#### **Product Information on Toxicological Effects:**

Acute Oral LD50: Unknown. Acute Dermal LD50: Unknown. Acute Inhalation LC50: Unknown. Ames Test: Unknown.

## **12. Ecological Information**

#### **Ecotoxicity:**

**Ecotoxicological Information:** Unknown. **Chemical Fate Information:** Unknown.

## **13.** Disposal Considerations

**Disposal Method:** Disposal should be made in accordance with federal, state, and local considerations.

## **14. Transport Information**

General:

DOT Shipping Name: Flammable Liquids, NOS DOT Hazard Class: Combustible Liquid DOT Label: NA UN/NA Label: UN1993 Placards: None IATA: NA IMO IMDG-code: NA European Class: RID (OCTI): NA ADR (ECE): NA RAR (IATA): NA

# **15. Regulatory Information**

#### **Regulatory Status and Applicable Laws and Regulations:**

SARA Section 302: None found.
SARA (311, 312) Hazard Class: None.
SARA (313) Chemicals: None.
CPSC Classification: NA
WHMIS Hazard Class: None.
Export Schedule:

B/HTSUS: 3910.00 Silicones in primary form.
ECCN: EAR99

California Proposition 65: None.
TSCA Inventory Status: All components are of this product are listed (or exempt) on the EPA TSCA inventory.

### Hazard Rating Systems:

HMIS (scale 0-4):

- Health = 1
- Flammability = 2
- Reactivity = 1

NFPA (scale 0-4):

- Health = 1
- Flammability = 2
- Reactivity = 1

## **16. Other Information**

**Revision Date:** 06/20/2016 **SDS Preparer:** Casey Linx

This product or its components are on the European inventory (EINECS) of existing commercial chemicals. This data is offered in good faith as typical values and not as a product satisfaction. No warranty, either expressed or implied, is made. The recommended handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use.

#### Abbreviations and Acronyms:

**OSHA:** Occupational Safety and Health Administration **ACGIH:** American Conference of Governmental Industrial Hygienists **LD50:** Lethal Dose, 50 percent LC50: Lethal Concentration, 50 percent

**DOT:** US Department of Transportation

IATA: International Air Transport Association

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)