

SS-55L

Product Description

SS-55L is a high temperature gasket dressing. Developed as a non-running gel sealant, this product provides high-tack properties to gaskets. SS-55L fills microscopic voids between the gasket and clamping surfaces. Unlike competitive offering, SS-55L will not lose physical properties when subjected to extreme temperatures.

Product Features

- Non-hardening
- High temperature >600°F
- Resists engine fluids
- Non-organic
- Considered safe in California

Typical Applications

- Gearbox assemblies
- Oil pans
- Transmission pans

Chemical Cure System

N/A



High Temperature Gasket Dressing

Typical Properties

Color Blue Specific Gravity 0.90

Consistency Thixotropic Gel

Odor None VOC's <1.0% Flashpoint >600°F

Solids

100% solids

Service Temperature

-45 to 260°C

Limitations

Ensure enough product remains between flanges to be effective in an assembly.

Handling and Safety

For maximum shelf life, keep containers sealed when not in use. Keep out of the reach of children. Uncured sealant irritates eyes and skin. Refer to the SDS.

Shelf Life

Sealed containers are guaranteed for 12 months from the ship date when stored in a cool dry area below $70^{\circ}F$.

Limited Warranty

All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as warranty, either expressed or applied. User shall rely on his/her own information and tests to determine suitability of the product for the intended use, and the user assumes all risk and liability resulting from the use of this product. Manufacturer's sole responsibility shall be to replace that portion of product that the manufacturer proves to be defective. Manufacturer shall not be liable to the buyer or any third party for injury, loss or damage directly or indrectly resulting from the use of, or inability to use, the product. Recommendations or statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding by the manufacturer.

This product has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses which implantation within the human body is intended.

*****Customized versions available upon request****